

Safety data sheet TPU 95A

Ultimaker

1. Identification of the substance/preparation and of the company

1.1 Trade name	TPU 95A
1.2 Use of the product	3D-Printer filament
1.3 Supplier	Ultimaker (Watermolenweg 2, 4191PN, Geldermalsen, The Netherlands)
Emergency phone number	In case of toxicological emergency contact your doctor

2. Hazards identification according to regulation (EC) No 1272/2008 and GHS

2.1 Classification of the substance or mixture	No risk exists to the health of users if the product is handled and processed properly
2.2 Label elements	
Labelling	Not applicable
2.3 Other hazards	Not known

3. Composition/information on ingredients

3.1 Composition	Thermoplastic polyurethane
3.2 Mixture	-

4. First aid measures

4.1 Description of first aid measures	General advice: If you feel unwell, seek medical advice (show the label where possible). Never give anything by mouth to an unconscious person
Inhalation	In case of inhalation of gases released from molten filament, move person into fresh air
Skin contact	Wash with soap and water. Seek medical attention if symptoms occur. If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water, do not try to peel it off and seek for medical attention, if necessary, for removal and treatment of the burns

Eye contact	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. Seek medical attention if symptoms persist. If molten material contacts the eye, immediately flush with plenty of water for at least 15 minutes. Seek medical attention immediately
Ingestion	Not probable. Seek medical advice in case ingestion occurs
Note to physician	Treat symptomatically
4.2 Most important symptoms and effects, both acute and delayed	Burns should be treated as thermal burns. The material will come off as healing occurs; therefore immediate removal from skin is not necessary
4.3 Indication of any immediate medical attention and special treatment needed	No data available
<u>5. Firefighting measures</u>	
5.1 Extinguishing media	Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or grounding procedures Foam, carbon dioxide (CO ₂), water, dry extinguishing media Unsuitable extinguishing media: not known
5.2 Special hazards arising from the substance or mixture	Burning produces obnoxious and toxic fumes: carbon oxides (CO _x), nitrogen oxides (NO _x), hydrogen cyanide (HCN), and isocyanate (RNCO)
5.3 Advice for firefighters	Use self-contained breathing apparatus and full protective clothing
<u>6. Accidental release measures</u>	
6.1 Personal precautions, protective equipment and emergency procedures	Avoid breathing gases released from molten filament. Ensure adequate ventilation, especially in confined areas
6.2 Environmental precautions	No data available
6.3 Methods and materials for containment and cleaning up	Allow molten material to solidify. Dispose waste and residue in accordance with local regulations
6.4 Reference to other sections	-
<u>7. Handling and storage</u>	
7.1 Precautions for safe handling	Avoid contact with molten material
7.2 Conditions for safe storage, including any incompatibilities	Product should be stored in a dry and cool place at temperatures between -20 to +30 °C and below 50% relative humidity. Avoid direct sunlight.
7.3 Specific end use(s)	Filament for 3D printing

8. Exposure controls/personal protection

8.1 Control parameters (*)

DNEL:

The regulations for the substances listed below must be observed when processing this product, particularly if processing takes place at elevated temperatures. In our experience printing in a well ventilated area will ensure compliance with the following occupational exposure limits:

- Aluminum oxide (CAS 1344-28-01) ≤ 0.03% : 1 mg/m³ (TLV)
- Carbon Black (CAS 1333-86-4) ≤ 0.05% : 3.5 mg/m³ (TLV)
- C.I. Pigment Black 28 (CAS 68186-91-4) ≤ 0.02% : 0.5 mg/m³ (TLV)
- Ethylene Bisstearamide (CAS 110-30-5) ≤ 0.2% : -
- Limestone (CAS 1317-65-3) ≤ 0.3% : 10 mg/m³ (TLV)
- Silicon Dioxide (CAS 7631-86-9) ≤ 0.05% : 10 mg/m³ (TLV)
- Titanium Dioxide (CAS 13463-67-7) ≤ 1.1% : 10 mg/m³ (TLV)

PNEC:

No data available
No data available

8.2 Exposure controls

Eye protection

Use safety glasses for prolonged stare at printing

Skin and body protection

Good practices suggest to minimize skin contact. When material is heated, wear gloves to protect against thermal burns

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (when applicable) or to an acceptable level (in countries where exposure limits have not been established) an approved respirator must be worn. Respirator type: air-purifying respirator with an appropriate government approved (where applicable) air purifying filter, cartridge or canister. Contact a health and safety professional or manufacturer for specific information

Hand protection

Follow good industrial hygiene practices

Hygiene measures

Follow good industrial hygiene practices

Engineering measures

Good general ventilation (typically 10 air changes per hour) is recommended. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls that maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance
Color
Odor
Flash point
Ignition temperature
Thermal decomposition
Auto-ignition temperature
Melting point/range
Density
Water solubility
Solubility in other solvents

Filament
White
Slight
-
Not self-igniting
> 230 °C
> 400 °C
220 °C
1.22 g/cm³
Insoluble
Tetrahydrofurane, dimethyl formamide, dimehtyl acetamide, N-methyl pyrrolidone, dimethyl sulphoxide, pyridine

(*) TLV (Threshold Limit Value)

9.2 Other information

-

10. Stability

Stable under recommended storage conditions

10.1 Reactivity

No data available

10.2 Chemical stability

This product is stable if stored and handled as indicated

10.3 Possibility of hazardous reactions

No decomposition or hazardous reactions if stored and applied as directed

10.4 Conditions to avoid

Print temperatures above 240 °C (at standard printing speeds)

10.5 Incompatible materials

Not known

10.6 Hazardous decomposition products

See 5.2

11. Toxicological information

11.1 Information on toxicological effects

Principle routes of exposure

Eye contact, skin contact, inhalation, ingestion

Acute toxicity

Oral (LD50; tested in rats; value: >5000 mg/kg)

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Reproductive toxicity

No known chronic effects

Carcinogenicity

The chemical structure does not suggest a specific alert for such an effect

12. Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

Poorly biodegradable

12.3 Bio accumulative potential

Does not significantly accumulate in organisms

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

No data available

13. Disposal considerations

13.1 Waste treatment methods

In accordance with local and national regulations

14. Transport information

ADR	-
RID	-
IATA	Not regulated
IMDG	Not regulated
Special precautions for user	Not regulated

15. Regulatory information

Not meant to be all inclusive - selected regulations represented

15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture

US Regulations:

Sara 313 title III	Not listed
TSCA inventory list	Listed
OSHA hazard category	Chronic target organ effects reported
CERCLA	Not reportable
WHMIS	-
State right-to-know requirements	-

Other inventories:

Canada DSL inventory list	-
REACH/EU EINECS	Components are in compliance with REACH and/or are listed
NEHAPS	Not regulated
Japan (ECL/MITI)	-
Australia (AICS)	-
Korean toxic substances control act (ECL)	-
Philippines inventory (PICCS)	-
Chinese chemical inventory (IECSC)	-

15.2 Chemical safety assessment

No data available

16. Other information

The information provided in this Safety Data Sheet (SDS) is based on current knowledge and experience. This information is provided without warranty. This information should help to make an independent determination of the methods to ensure proper and safe use and disposal of the filament

Version Version 3.006

Date 18/04/2017

Ultimaker