

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Laser T	Thins	
Product Synonym(s): M	licro-Surfaced Impact Acrylic	
Chemical Family: Acry	lic Copolymer	
Chemical Formula: Mix	ture	
Chemical Name: Mixtu	re	
EPA Reg Number:		
Product Use: Interior/E	xterior Signage, Personal Identification, Other	
Manufactured By:	Innovative Plastics Inc.® (IPI®)	EMERGENCY PHONE NUMBERS:
	P.O. Box 7065	Medical: 911
	Algonquin, IL 60142, USA	Poison Control: 800-222-1222
Telephone Numbers	Available Hours	Phone Number

<u>Telephone Numbers</u>	Available Hours	Phone Number
IPI Customer Service	8:30am-4:30pm CST	1-815-477-0778

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient Name	CAS Registry Number	Typical Wt. %	<u>OSHA</u>
P (EA/MMA)	Proprietary	50-54	Ν
Acrylic Styrene Copolymer	Proprietary	35-50	Ν
Ethyl acrylate	140-88-5	< 0.1	Y
Methyl methacrylate	80-62-6	< 0.5	Y
Carbon Black	1333-86-4	1-5	
Copper	7440-50-8	1-5	
Aluminium Flake	7429-90-5	1-5	

The ingredient(s) marked with a "Y" in the OSHA column are recognized as hazardous chemicals according to the criteria of the OSHA Hazardous Communication Standard (29 CFR 1910.1200).

While this material is not classified as hazardous under Federal OSHA regulations, this MSDS contains valuable information critical to the proper handling and correct use of this product. This MSDS should be retained and accessible for employees and other users of this product.

The ingredients of this product are all on the TSCA Inventory list.

3. HAZARDS INDENTIFICATION

EMERGENCY OVERVIEW:

Sheet material, various sizes, and mild odor. CAUTION! MELT PROCESSING RELEASES VAPORS WHICH MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION

POTENTIAL HEALTH EFECTS:

Skin contact and inhalation of dust are expected to be the primary routes of occupational exposure to this material. Due to its chemical and physical properties, this material does not require special handling other than the good industrial hygiene and safety practices employed with any industrial material of this type.

Ethyl acrylate is listed as a substance that may reasonably be anticipated to be a carcinogen by the National Toxicology Program (NTP) and is classified as "possibly carcinogenic to humans" by the International Agency for Research on Cancer.

4. FIRST AID MEASURES

IF IN EYES:

Flush eyes with plenty of water; remove contact lenses after the first 1-2 minutes then continue flushing for several minutes. Only mechanical effects expected. Get medical attention if irritation persists.

IN CASE OF CONTACT:

If molten material comes in contact with the skin, do not apply ice but cool under running stream of water. DO NOT attempt to remove the material from the skin. Removal could result in severe damage. Wash clothing before reuse. Get medical attention if irritation develops and persists.

5. FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES:

Auto-Ignition Temperature 393 C/739 F Flash Point – NA Flash Point Method Flammable Limits: Upper – NA Lower –NA

EXTINGUISHING MEDIA:

Water fog or spray, foam, dry chemical or carbon dioxide.

FIRE FIGHTING INSTRUCTIONS:

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand NIOSH approved or equivalent). Fire fighting equipment should be thoroughly decontaminated after use.

FIRE AND EXPLOSION HAZARDS:

Heated material can form flammable vapors with air.

6. ACCIDENTAL RELEASE MEASURES

IN CASE OF SPILL OR LEAK:

Contain spill. Sweep or scoop up and remove to suitable container. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

7. HANDLING AND STORAGE

HANDLING:

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container closed. Use only with adequate ventilation.

STORAGE:

Avoid temperature extremes during storage; ambient temperature preferred.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS:

Adequate ventilation in work area is needed due to dust or vapors created during fabrication.

PERSONAL PROTECTIVE EQUIPMENT (PPE):

EYE/FACE PROTECTION:

Safety glasses or face shield should be used. If exposed to dust, chemical glasses may be required.

SKIN PROTECTION:

No precautions other than clean body-covering clothing should be needed. Use insulated gloves for thermal protection, when desired.

RESPIRATORY PROTECTION:

In dusty atmospheres, use an approved respirator.



Date: 05/09/2012

MSDS #3

MATERIAL SAFETY DATA SHEETS

9. PHYSICAL AND CHEMICAL PROPERTIES

<u>APPEARANCE/ODOR:</u> Various colors, characteristic odor

BOILING POINT: N/A

<u>VAPOR PRESSURE:</u> N/A

VAPOR DENSITY: N/A

SPECIFIC GRAVITY: 1.15-1.19

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable

<u>CONDITIONS TO AVOID:</u> Prolonged contact with acids, alkalis and strong oxidizing agents may attack or dissolve the polymer.

11. TOXICOLOGY INFORMATION

No data available

12. ECOLOGICAL INFORMATION

MOVEMENT & PARTITIONING:

In the terrestrial environment, material is expected to remain in the soil. In the aquatic environment, material will sink and remain in the sediment.

DEGRADATION & PERSISTENCE:

This water insoluble polymeric solid is expected to be inert in the environment. Surface photo degradation is expected with exposure to sunlight. No appreciable biodegradation is expected.

ECOTOXICITY:

Not expected to be acutely toxic, but chips may mechanically cause adverse effects if ingested by waterfowl or aquatic life.

13. DISPOSAL CONSIDERATIONS

Disposal must be in accordance with applicable governmental regulations.

14. TRANSPORT INFORMATION

DEPARTMENT OF TRANSPORTATION (D.O.T.):

This product is not regulated by D.O.T. when shipped domestically by land.

CANADIAN TDG INFORMATION:

This product is not regulated by TDG when shipped domestically by land.



MATERIAL SAFETY DATA SHEETS

(Not meant to be all-inclusive – selec	ted regulations represented)		
Hazard Categories Under Criteria of S	SARA Title III Rules (40 CFR	Part 370)	
Immediate (Acute) Health N Sudden Release of Pressure N Fire	Delayed (Chronic) Health Reactive N	N N	
The components of this product are al	ll on the TSCA inventory list.		
INGREDIENT RELATED REGULA SARA REPORTABLE QU Ethyl acrylate Methyl methacrylate P (EA/MMA)		A RQ SARA TPQ 1000 LBS 1000 LBS N/A	N/A
SARA TITLE III, SECTION 313 This product does contain chemical(s 313 of Title III of the Superfund Ame Ethyl acrylate Aluminium			ct to the reporting requirements of, Section Part 372. See Section 2
CALIFORNIA PROP 65 – CARCINO This product does contain the followi Ethyl acrylate Mercury		clow, currently on the Cal Toluene	ifornia list of Known Carcinogens.
This product may contain trace levels Antimony (3+) Trioxide Cadmium 3.3'-Dichlorobenzidine Lead Selenium Sulphide	of components known to the s	Arsenic	e cancer:
MASSACHUSETTS RIGHT TO KN This product does contain the followi List.		elow, currently on the M	assachusetts Right to Know Substance
Ethyl acrylate		Methyl methacrylate	
Antimony (3+) Trioxide Cadmium		Arsenic Chromium (3+), (6+)	
3.3'-Dichlorobenzidine		Formaldehyde	
Lead Vinyl Acetate		Nickel	
PENNSYLVANIA RIGHT TO KNO This product does contain the followi Ethyl acrylate Chromium (3+)		low, currently on the Per Methyl methacrylate Formaldehyde	nnsylvania Hazardous Substance List.
NEWJERSEY RIGHT TO KNOW	ng chemical(s), as indicated be	-	w Jersey Right-to-Know Substances List.
PENNSYLVANIA ENVIRONMENT This product does contain the followi Ethyl acrylate		low, currently on the Per Methyl methacrylate	nnsylvania Environmental Hazard List.
PENNSYLVANIA SPECIAL HAZA This product does contain the followi Ethyl acrylate		blow, currently on the Per	nnsylvania Special Hazard List.
1 <i>P</i> 1.			

Date: 05/09/2012

MATERIAL SAFETY DATA SHEETS

16. OTHER INFORMATION

NFPA HAZARD RATING (National Fire Protection Association):

Fire 1 Health 0 0 Reactivity	FIRE: Must be preheated before ignition can occur. <u>HEALTH:</u> Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials. <u>REACTIVITY:</u>
- Crossiel	

REASON FOR ISSUE:

Innovative Plastics Inc. (IPI) believes that the information provided (including data and statements) are accurate as of the date hereof. No warranty, express or implied, is made concerning the information provided. Contact IPI for further information.



Date: 05/09/2012

MSDS #3